

TITLE

sgg COOL- LITE® KS150II

SUBTITLE

Solar control and low emissivity glass



DESCRIPTION

see COOL- LITE KS150II is high light reflectance curved temperable solar control coated glass. With good solar control performance, it can keep interiors more comfortable by preventing excessive solar in summer, environmentallyfriendly cooling solution with less need for costly air- conditioning.

RANGE

Product	Thickness	hickness Dimension			
K\$150II	5mm	3050mm*2134mm/2440mm 3300mm*2134mm/2440mm			
	6/8/10mm	3050mm*2134mm/2440mm 3300mm*2134mm/2440mm 3660mm*2540mm			
	12mm	3050mm*2134mm/2440mm 3300mm*2134mm/2440mm			

Max : 6mm(4200mm*2440mm) 8mm/10mm(4200mm/4500mm*2440mm)

PERFORMANCE

Product	Structure	Face	Louminous factor (%)		sc	U value (W/m²·K)	
			TL	RLe	SC	Air	Argon
KS 150 II	6-9-6	2	46	29	0.40	1.9	1.5
	6-12-6	2	46	29	0.39	1.6	1.3

PRODUCT APPLICATION
Offices and commercial buildings Industrial buildings Hotels and restaurants Schools and Hospitals

ADVANTAGE

Proper light transmission levels and higher reflectance.

Spectrally selective glasses combining proper light transmission levels with a low solar facor, thus reducing air conditioning costs.

Provide excellent thermal insulation properties when assembled into double- glazed units.

Have a silver grey apperance with high light reflectance when produced on a clear substrate.