

#### TITLE

sgg COOL- LITE® SKN 163II

#### SUBTITLE

High performance solar control glass with advanced thermal insulation properties



### **DESCRIPTION**

see COOL- LITE SKN163 II, the high performance curved temperable double silver coating, allows the light through while reducing the solar heat, making it ideal for commercial glazing where high levels of light transmittance coupled with a low solar factor are required.

see COOL- LITE SKN 163 II is a solar control glass, which blocks up to 67% of solar heat by reflecting it to the outside. It can be for use in residential or commercial buildings alike, either for façades or overhead glazing.

#### **RANGE**

Product	Thickness	Dimension			
SKN163II	5mm	3050mm*2134mm/2440mm 3300mm*2134mm/2440mm			
	6/8/10mm	3050mm*2134mm/2440mn 3300mm*2134mm/2440mn 3660mm*2540mm			
	12mm	3050mm*2134mm/2440mm 3300mm*2134mm/2440mm			

Max : 6mm(4200mm\*2440mm) 8mm/10mm(4200mm/4500mm\*2440mm)

# PERFORMANCE

Product	Structure	Face	Louminous factor (%)		sc	U value (W/m²·K)	
			TL	RLe	30	Air	Argon
SKN163 II	6-12-6	2	58	15	0.40	1.6	1.2
	6-16-6	2	58	15	0.39	1.3	1.0

# PRODUCT APPLICATION

Offices and commercial buildings Industrial buildings Hotels and restaurants Schools and Hospitals Conservatiories and atria glazing

### **ADVANTAGE**

More environmentally-friendly cooling solution with less need for costly air-conditioning or blinds. Gently filters light to reduce uncomfortable glare from direct sun rays, whilst still allowing in plenty of natural light. Excellent thermal insulation to reduce the need for internal heating during colder months.