

TITLE

sgg COOL- LITE® KT155

SUBTITLE

Solar control and low emissivity glass



DESCRIPTION

seg COOL- LITE KT155 is solar control and low- e coated glass. With good level of light transmittance and proper solar control performance, it makes interiors more comfortable in summer, hence reducing air- conditioning costs. Enjoy nature view, with gently filters light to reduce uncomfortable glare from direct sun rays, whilst still allowing in plenty of natural light.

RANGE

Product	Thickness	Dimension		
KT155	5mm	3050mm*2134mm/2440mm 3300mm*2134mm/2440mm		
	6/8/10mm	3050mm*2134mm/2440mm 3300mm*2134mm/2440mm 3660mm*2540mm		
	12mm	3050mm*2134mm/2440mm 3300mm*2134mm/2440mm		

Max : 6mm(4200mm*2440mm) 8mm/10mm(4200mm/4500mm*2440mm)

PERFORMANCE

Product	Structure	Face	Louminous factor (%)		sc	U value (W/m²-K)	
			TL	RLe	30	Air	Argon
KT155	6-9-6	2	47	17	0.43	2.2	1.8
	6-12-6	2	47	17	0.43	1.9	1.6

PRODUCT APPLICATION
Offices and commercial buildings Industrial buildings Hotels and restaurants Schools and Hospitals

ADVANTAGE

Spectrally selective glasses combining good light transmission levels with a low solar facor, thus reducing air conditioning costs.

Have a blue grey apperance when produced on a clear substrate, make intelligent design for architects. Environment friendly, eco application